

CFEP HEAT SHRINK TUBING

CFEP heat shrink tubing is used where many of the properties of CTFE HS are desired but the shrink temperature must be lower. CFEP HS has a temperature rating of -55C to 200C and shrinks at 290C.

FEP 1.3-1 Shrink Ratio

AWG Size	Exp. Inside Diameter	Rec. Inside Diameter	Rec. Wall Thickness
24	.031	.027	.008
22	.036	.032	.008
20	.045	.039	.008
18	.060	.049	.008
16	.075	.061	.009
14	.092	.072	.009
12	.115	.089	.009
10	.141	.114	.010
9	.158	.124	.010
8	.180	.143	.010
7	.197	.158	.011
6	.225	.180	.011
5	.248	.198	.011
4	.290	.226	.011
3	.310	.249	.011
2	.365	.280	.012
1	.400	.311	.012
0	.440	.349	.012
Fractional Size			
3/8"	.500	.383	.015
7/16"	.580	.448	.020
1/2"	.666	.510	.020
5/8"	.830	.637	.025
3/4"	1.000	.764	.030
7/8"	1.170	.891	.035
1"	1.330	1.020	.035
1-1/8"	1.500	1.145	.035
1-1/4"	1.666	1.270	.035
1-3/8"	1.833	1.390	.035
1-1/2"	2.000	1.520	.035

M23053/11 cl 1

FEP 1.6-1 Shrink Ratio

AWG Size	Exp. Inside Diameter	Rec. Inside Diameter	Rec. Wall Thickness
3/32"	.093	.056	.008
1/8"	.125	.075	.010
3/16"	.188	.115	.010
1/4"	.250	.150	.010
3/8"	.375	.225	.012
1/2"	.500	.300	.015
3/4"	.750	.450	.020
1"	1.000	.600	.025
1-1/2"	1.500	.900	.030
2"	2.000	1.200	.030

M23053/11

* Natural clear tubing is standard (1-2 week lead-time), colors available-white, yellow, orange, green, black, blue, red, brown, violet, gray, call for quote and lead-time. Minimum order quantity : 100 feet for AWG sizes and 24ft for fractional sizes.